

AC/DC power supplies

MAA Family **MAA3000 NEW, 3000 W**



Basic specifications

Power	3000 W
Input current	up to 125 A
Input voltage	~220 (187...264) VAC
Output voltage	=24 VDC, =28VDC, =48VDC
Efficiency.....	91-92%
Case operating temperature.....	-40...+85 °C; -50...+85 °C
Dimensions	284×174×54 mm
Warranty	2 years

Advantages

- ◀ MIL-STD-461E without external components
- ◀ MIL-STD-810G
- ◀ Parallel and series operation
- ◀ Output voltage adjustment
- ◀ Conductive cooling
- ◀ DC OK
- ◀ Stand-by power supply



Description of MAA3000 on the manufacturer's website:
eng.kwsystems.ru/catalog/acdc/models/76


Order registration

+7 473 200 87 80, Global Operations Team

Technical support

Mikhail Timokhin, mtimohin@kwsystems.ru

Ordering information



Input specifications*

Parameter	Value
Input voltage range, VAC*	187...242 (263...340 VDC)
Transient deviation range, VAC	~176...264
Transient time	1 s.
Mains frequency range, Hz	47...440
Consumed current, A	15
Power factor corrector	+
Power factor	0.9

Output specifications*

Parameter	Value		
Model	MAA3000-1S24-SXX	MAA3000-1S28-SXX	MAA3000-1S48-SXX
Nominal output voltage, VDC	24	28	48
Output voltage adjustment	10 %		
Rated output power, W	3000**		
Efficiency, %	91	91	92
Output voltage adjustment range, MCB	by built-in trim resistor	-10...+10 %	-10...+10 %
Rated output current, A	125	107.14	62.5
Ripple and noise (peak-to-peak)	<2%		
Line and load regulation	max 2%		
Start-up time, ms	<2000		
Parallel operation	redundancy, and boost of power		
Remote on/off	Off at 3.5...5.5 VDC (15...30 mA) output «REMOTE OFF»		
Maximum load capacity	36500 µF (Uout=28 VDC, Pout=50%)		

* All specifications are valid for normal climatic conditions (ambient temp. +15...+35°C; relative humidity 45...80%; air pressure 8.6*10⁴...10.6*10⁴ Pa), Uin. nom., Iout. nom., unless otherwise noted.

Protections

Type of protection	
Short-circuit protection*	auto recovery
Overload protection	$P_{max} < 1.2 P_{nom}$
Overvoltage protection level*	$< 125\% U_{out nom.}$
Overheat protection	triggers at case temperature $> 85^{\circ}\text{C}$

Basic specifications**


Parameter		Value
Type of connection		screw terminals and blade contacts
Derating		$-3.3\% / ^{\circ}\text{C}$ ($t^{\circ} < 40^{\circ}\text{C}$ and $> 70^{\circ}\text{C}$)
Protection level		IP20
Case temperature, operating	«N»	$-40...+85^{\circ}\text{C}$
	«P»	$-50...+85^{\circ}\text{C}$
Case temperature, storage		$-50...+70^{\circ}\text{C}$
Humidity		98% / 35°C
Isolation voltage	in /case	$\sim 1500\text{ VAC}$
	in /out	$\sim 1500\text{ VAC}$
	out /case, out/out	$\sim 500\text{ VAC}$
Isolation resistance @ 500 VDC		$\geq 20\text{ MOhm min}$
Cooling		conductive, forced air
Environmental influence standards		design to meet MIL-STD-810G
EMC standards		MIL-STD-461E
Typical MTBF		3 000 000 Hrs
Case material		metal
Dimensions, mm		284×174×54
Weight, kg		< 3.4
Warranty		2 year

* Parameters are stated for the information purposes and could not be used at long term work, exceeding maximum output current, operating outside of a working temperatures range or when output voltage is over the range of adjustment.

** All specifications are valid for normal climatic conditions, $U_{in nom.}$, $I_{out nom.}$, unless otherwise noted.

Derating

vs Temperature




Decreasing parts of the dashed and dash-dotted curves correspond to the maximum case temperature (+85°C for models with index "N" and "P"). Output power must not exceed the values limited by curve for a given ambient temperature.

Modules can be used without the heatsink only on condition of installation with thermal grease on heat-distribution baseplate with length and width not less than case's and with thickness not less than 8 mm.

Dimensions

Single-channel design with blade contacts




1	2	3	4	5	6	7	8	9	10	11	12	13
L	N	GND	-REMOTE OFF	+REMOTE OFF	AUX	+RS	-RS	PARAL	TRIM	+DIAG OUT	-DIAG OUT	+FAN

14	15	16	17	18	19	20	21	22	23
-FAN	NOT USE	+Uout1	+Uout1	+Uout1	+Uout1	-Uout1	-Uвых1	-Uout1	-Uout1

Dimensions

Single-channel design with terminal blocks



X1			X2				X3			X4		
1	2	3	1	2	3	4	1	2	3	1	2	3
L	N	GND	+Uout1	+Uout1	-Uout1	-Uвых1	+FAN	-FAN	NOT USE	-REMOTE OFF	+REMOTE OFF	AUX

X5				X6	
1	2	3	4	1	2
+RS	-RS	PARAL	TRIM	+DIAG OUT	-DIAG OUT



www.kwsystems.ru info@kwsystems.ru

KW Systems, LLC is the leading Russian developer and manufacturer of AC/DC converters and power supply systems for mission critical applications.

Druzinnikov str. 5B, Voronezh, 394026, Russia. +7 473 200-87-80